

INDUSTRIAL PLATINUM RESISTANCE THERMOMETER

beamex
A BETTER WAY TO CALIBRATE



Beamex IPRT-300 Pt100 probe

The Beamex IPRT-300 is a robust industrial general-purpose temperature probe. It can be used up to +300°C (+572°F) temperature. The IPRT-300 provides a good accuracy of ± 0.04 °C when used with the provided CvD coefficients. The probe is a standard IEC60751 Pt100 (385) probe, so it can be used also without correction

coefficients, providing better than 1/5 DIN accuracy. The IPRT-300 is provided with a Lemo connector, so it can be plugged in to Beamex MC6 family calibrators and Beamex dry blocks. The probe comes with an accredited calibration certificate with the CvD coefficients included as standard.

MAIN FEATURES:

- A robust industrial temperature probe for multiple purposes
- Temperature range -45 °C ... $+300$ °C (-49 °F ... 572 °F)
- Accuracy up to ± 0.04 °C with CvD coefficients
- Provided with a 6 Pin connector compatible with Beamex MC6 family calibrator and Beamex dry blocks
- Comes with an accredited calibration certificate with CvD coefficients included



SPECIFICATIONS

FEATURE	SPECIFICATION
Structure	Pt100 4-wire connection wire wound in stainless steel casing
Temperature range	-45 °C ... $+300$ °C (-49 °F ... 572 °F)
Accuracy (with CvD coefficients) ⁽¹⁾	0.04 °C
Accuracy (without CvD coefficients) ⁽¹⁾	0.06 °C + 0.1% RGD (1/5 IEC 60751 class B)
Dimensions	\varnothing 3 mm x 250 mm (0.12" x 9.84")
Cable	3.0 m (9.84') long Teflon/Silicon cable
Connector	6 Pin Lemo connector, compatible with several Beamex products
Weight	~ 110 g (0.24 lb)
Calibration	Accredited calibration certificate included as standard, including the CvD coefficients
Warranty	1 year

1) Excluding calibration uncertainty

To use the IPRT-300 probe with a calibrator with four banana plugs, please use the adapter (code 8120500) available as an optional accessory.

70977346759834759843
87984654546546
7987465465465132132131
62567965836458734657
665387875684653400